

## TWISTFIX LIFE LINE SYSTEM



### Product information

- Tested for metal, concrete, wooden roof structures
- Easy to waterproof
- Innovative and patented energy absorber
- Two persons between each line section
- Certified by DEKRA Exam GmbH
- EN-795:2012 type C & TS 16415:2013
- Each post is labelled with a unique ID-number
- Product warranty 15 years

### Technical information

- Toggle bolts for Wooden and Metal roof structures
- Mechanical anchor for Concrete structures
- Fall forces to roof structure < 11 kN
- Posts height 20 cm
- Posts Aluminium and yellow colour coated
- Brackets and Steel Wire made of Stainless Steel
- Dynamic posts
- Shuttle ATEX approved Guideline 2014/34/EU.

### Pictures of Line System parts



End post



Energy Absorber



Intermediate post



Tensioner






Corner post



Shuttle

### Marking & information



### Calculating your fall arrest and safe working height

Calculations using a fall arrest lanyard fixed at foot level

	2m Lanyard	1.5m Lanyard
Lanyard Length	2m	1.5m
Energy Absorber	1.75m	1.75m
Body Height	2m	2m
Deflection Line	1.5m	1.5m
Safety Distance	1m	1m
Minimum Clearance	8.25m	7.5m

